





final report

Project code: A.MQT.0055

Prepared by: Jodie Hill

Sensory Solutions

Date submitted: July 2011

PUBLISHED BY
Meat & Livestock Australia
Limited Locked Bag 991
NORTH SYDNEY NSW 2059

Meat app development – Stage 1

Providing the time and temperature data for modelling analysis for development of the iPhone app

Meat & Livestock Australia acknowledges the matching funds provided by the Australian Government and contributions from the Australian Meat Processor Corporation to support the research and development detailed in this publication.

This publication is published by Meat & Livestock Australia Limited ABN 39 081 678 364 (MLA). Care is taken to ensure the accuracy of the information contained in this publication. However MLA cannot accept responsibility for the accuracy or completeness of the information or opinions contained in the publication. You should make your own enquiries before making decisions concerning your interests. Reproduction in whole or in part of this publication is prohibited without prior written consent of MLA.

Contents

| Section | | Page |
|---------|------------------------------|------|
| 1 | Background | 3 |
| 1.1 | Reasoning behind the project | 3 |
| 2 | Methodology | 4 |
| 2.1 | Overall measures | |
| 2.2 | Cooking protocols | 5 |
| 3 | Results | 10 |
| 3.1 | Data | 10 |
| 4 | Next steps | 10 |
| 4.1 | Next steps | 10 |

1 Background

1.1 Reasoning behind the project

MLA is trying to build an iPhone software program (APP) which will assist consumers in cooking red meat more accurately and more consistently. Sensory Solutions was asked to assist in defining and discerning the parameters for cooking steak in a number of different ways.

Over time, MLA would like to build the specifications for cooking a number of meat cuts according to the following parameters;

| Cut of Meat | Thickness | "Doneness" | CookType |
|-------------|-----------|-------------|----------------|
| Tenderloin | 10mm | Rare | Electric stove |
| Cube Roll | 20mm | Medium Rare | Gas stove |
| Striploin | 30mm | Medium | Gas BBQ |
| Rump | 40mm | Medium Well | |
| | | Well Done | |

Stage 1 of the research focussed on cooking the products on the electric stove, this stage was not only used to develop the parameters of cooking, but also to obtain learning's in terms of understanding issues which may arise between how a consumer may cook the meat compared to the internal MLA protocols and thus development also of the final cooking protocols.

2 Methodology

2.1 Overall measures

Sensory Solutions will, as far as possible cook the meats according to the MSA cooking protocols. The following measures were taken;

- Cook time and rest time, including when to turn the meats.
- Cook temperature / Cook setting / Rate of convection (based on how long it takes to bring 500mL water to the boil).
- Internal temperature of the meat at specified times, including after rest.
- Weight & approximate size of the individual pieces of meat.

Figure 1: Weighing / measuring the meat cuts





Figure 2: Cooking set up in the kitchen - electric stove top



2.2 Cooking protocols

The following protocols were developed with MLA;

 Steaks were provided to Sensory Solutions pre-sliced into similar sizes (within cut of meat) and pre-determined thicknesses (as per the design). It must be noted that the oyster blade was eliminated from the study due to inconsistencies in the cut and because it was determined to be an unlikely grilling / frying cut.




Figure 3: Cuts of meat provided

- 2. Steaks were all brought to an internal temperature of 8-10°C prior to cooking.
- 3. Pan was pre-heated to hot for all steaks to start the cooking process. Once hot, pan temperature was dropped just before placing the steaks into the pan.
- 4. No more than two steaks were cooked in the pan at once.
- 5. Cut of meat was sprayed with oil, rather than the pan.

- 6. Cooked to specified degree of doneness;
 - o Rare: Turned only once and cooked until "very soft" with the back of tongs.

Figure 4: Example of RARE cooked meat



 Medium Rare: Cooked on one side until moisture visible on top surface.
 Meat is turned once and cooked until moisture visible on top and steak felt "soft" with the back of tongs.

Figure 5: Example of MEDIUM RARE cooked meat



 Medium: Cooked on first side until moisture pooling on top surface. Meat is turned once only and cooked on the second side until moisture visible and steak feels

"springy" with the back of the tongs.

Figure 6: Example of MEDIUM cooked meat



 Medium Well Done: Cooked on first side until moisture pooling on top surface. Meat is turned once only and cooked on the second side until moisture visible and steak feels "firm" with the back of the tongs.

Figure 7: Example of MEDIUM WELL cooked meat



Well Done: Cooked on first side until moisture pooling on top surface. Meat is turned once only and cooked on the second side until moisture visible. Reduce the heat and continue to cook until the steak feels "very firm" with the back of the tongs.






- 7. Additional steps for thicker (30mm and 40mm) steaks which were cooked beyond medium were introduced. The meat was cooked to medium and then removed from the stovetop and placed in the oven at 160 180□C until cooked appropriately. Measures were also taken for cooking this thicker and better done meat cooked entirely in the pan.
- 8. Once cooked, the meat was covered in foil and then allowed to rest.

Figure 9: Meat at rest



9. All measures were documented and provided to the MLA in an excel file.





3 Results

3.1 Data

All data was provided to MLA in an excel spreadsheet to assist in the development of a model to provide cooking instructions in an application for an i-phone.

Figure 11: Recording the data



4 Next steps

4.1 Next steps

Next steps are to provide the same information for a gas stove top and gas BBQ.